

# 仕様書

## Specification

項目 Item	内容 Specifications		
名称 Type	張力式ガス放出防止型高圧ホース High pressure hose incorporated with a tensile triggered shut-off valve		
型式 Model	T I H - 6 - 1 0 H Q	T I H - 6 - 1 0 S	T I H - 6 - 1 0 T
入口圧力 Inlet Pressure	1 . 5 6 MP a 以下 or less		
気密 Air-Tightness Test	1 . 8 0 MP a		
耐圧 Hydrostatic Test	2 . 7 0 MP a		
入口接続 Inlet Connection	P O L 継手 (手締め) (JIS POL with Handwheel)	P O L 継手 (スパナ締め) (JIS POL with POL Nut)	P O L 継手 (手締め) (JIS POL with Handwheel)
出口接続 Outlet Connection	R 1 / 4		
使用温度範囲 Working Temperature Range	- 2 5 ~ 6 0 °C		
質量 Product Weight	約 0 . 3 5 k g Approx.	約 0 . 3 5 k g Approx.	約 0 . 3 9 k g Approx.
備考 Note	口径 φ 6 全長 1 0 5 0 mm Internal Diameter φ 6 Overall Length 1 0 5 0 mm		

DATE: Aug.18.2023

 I·T·O 株式会社

[  ITO Corporation ]

東大阪市箱殿町 1 0 番 4 号  
10-4 Hakodono-cho, Higashi-Osaka City, Japan  
TEL:072-981-3781 FAX:072-987-6590