

仕様書

Specification

項目 Item	内容 Specifications		
名称 Type	張力式ガス放出防止型高圧ホース High pressure hose incorporated with a tensile triggered shut-off valve		
型式 Model	T I H - 6 - 6 H Q	T I H - 6 - 6 S	T I H - 6 - 6 T
入口圧力 Inlet Pressure	1. 5 6		M P a 以下 or less
気密 Air-Tightness Test	1. 8 0		M P a
耐圧 Hydrostatic Test	2. 7 0		M P a
入口接続 Inlet Connection	P O L 継手 (手締め) (JIS POL with Handwheel)	P O L 継手 (スパナ締め) (JIS POL with POL Nut)	P O L 継手 (手締め) (JIS POL with Handwheel)
出口接続 Outlet Connection	R 1 / 4		
使用温度範囲 Working Temperature Range	- 2 5 ~ 6 0 ° C		
質量 Product Weight	約 Approx. 0. 2 8 k g	約 Approx. 0. 2 8 k g	約 Approx. 0. 3 2 k g
備考 Note	口径 φ 6 全長 6 5 0 mm Internal Diameter φ 6 Overall Length 6 5 0 mm		

DATE: Aug.18.2023

 I·T·O 株式会社

[ ITO Corporation]

東大阪市箱殿町 1 0 番 4 号
10-4 Hakodono-cho, Higashi-Osaka City, Japan
TEL:072-981-3781 FAX:072-987-6590