

# 仕 様 書

## Specification

項 目 Item	内 容 Specifications	
名 称 Type	二段式二次用調整器 Second Stage Regulator	
型 式 Model	A C - 1 5	
容 量 Capacity	1 5 m <sup>3</sup> /h ( n o r m a l ) : NH <sub>3</sub>	
入口圧力 Inlet Pressure	0 . 0 7 ~ 0 . 1 5	M P a
出口圧力 Outlet Pressure	2 . 3 0 ~ 3 . 3 0	k P a
閉塞圧力 Lockup Pressure	3 . 5 0	k P a 以下 or less
安全弁作動圧力 Safety Relief Valve Working Pressure	吹き始め Start-to-discharge	5 . 6 0 ~ 8 . 4 0 k P a
	吹き止まり Stop-to-discharge	5 . 0 4 ~ 8 . 4 0 k P a
気密 Air-Tightness Test	入口側 Inlet	0 . 3 0 M P a
	出口側 Outlet	5 . 5 0 k P a
耐圧 Hydrostatic Test	入口側 Inlet	0 . 8 0 M P a
	出口側 Outlet	0 . 3 0 M P a
入口接続 Inlet Connection	R c 1 / 2	
出口接続 Outlet Connection	R c 1 / 2	
面間寸法 Spacing Dimension	9 0	m m
使用温度範囲 Working Temperature Range	- 5 ~ 6 0 °C	
質量 Product Weight	約 Approx.	4 k g
備考 Note		

DATE: Dec.16.2016

**Ⓢ I·T·O株式会社**

[ **Ⓢ I·T·O Corporation** ]

(10-4 Hakodono-cho, Higashi-Osaka City, Japan)

TEL:072-981-3781 FAX:072-987-6590