

# 仕 様 書

## Specification

項 目 Item	内 容 Specifications	
名 称 Type	二段式二次用調整器 Second Stage Regulator	
型 式 Model	G L - 7 0 - 2	
容 量 Capacity	7 0 k g / h : C <sub>3</sub> H <sub>8</sub>	
入口圧力 Inlet Pressure	0. 0 2 5 ~ 0. 1 0	M P a
出口圧力 Outlet Pressure	2. 3 0 ~ 3. 3 0	k P a
閉塞圧力 Lockup Pressure	3. 5 0	k P a 以下 or less
安全弁作動圧力 Safety Relief Valve Working Pressure	吹き始め Start-to-discharge	5. 6 0 ~ 8. 4 0 k P a
	吹き止まり Stop-to-discharge	5. 0 4 ~ 8. 4 0 k P a
気密 Air-Tightness Test	入口側 Inlet	0. 3 0 M P a
	出口側 Outlet	5. 5 0 k P a
耐圧 Hydrostatic Test	入口側 Inlet	0. 8 0 M P a
	出口側 Outlet	0. 3 0 M P a
入口接続 Inlet Connection	J I S 1 0 K 2 5 A	フランジ Flange
出口接続 Outlet Connection	R c 1 1 / 4	ユニオン Union
面間寸法 Spacing Dimension	3 6 5	m m
使用温度範囲 Working Temperature Range	- 5 ~ 6 0	° C
質量 Product Weight	約 Approx.	7 k g
備考 Note		

DATE: Dec.16.2016

**Ⓢ I・T・O株式会社**

[ **Ⓢ I・T・O Corporation** ]

(10-4 Hakodono-cho, Higashi-Osaka City, Japan)

TEL:072-981-3781 FAX:072-987-6590