

# 仕 様 書

## Specification

項 目 Item	内 容 Specifications		
名 称 Type	ガバナ Pressure Governor		
型 式 Model	S G - 3 2 B		
容 量 Capacity	8 0 m <sup>3</sup> /h ( n o r m a l )	(比重：1) (Specific Gravity)	
入口圧力 Inlet Pressure	5. 8 0 ~ 3 5. 0	k P a	
出口圧力 Outlet Pressure	2. 5 5 ~ 3. 0 5	k P a	
閉塞圧力 Lockup Pressure	3. 4 0	k P a	以下 or less
安全弁作動圧力 Working Pressure	吹き始め Start-to-discharge	5. 6 0 ~ 8. 4 0	k P a
	吹き止まり Stop-to-discharge	5. 0 4 ~ 8. 4 0	k P a
気密 Air-Tightness Test	入口側 Inlet	0. 0 4	M P a
	出口側 Outlet	5. 5 0	k P a
耐圧 Hydrostatic Test	入口側 Inlet	0. 0 7	M P a
	出口側 Outlet	0. 0 3	M P a
入口接続 Inlet Connection	R c 1 1 / 2		
出口接続 Outlet Connection	R c 1 1 / 2		
面間寸法 Spacing Dimension	2 1 2	m m	
使用温度範囲 Working Temperature Range	- 5 ~ 6 0		° C
質量 Product Weight	約 Approx. 1 2. 3		k g
備考 Note	<ul style="list-style-type: none"> <li>• 入口圧力範囲：1. 0 0 ~ 3 5. 0 k P a (Inlet Pressure Range : 1.00~35.0kPa)</li> <li>• 出口圧力調整範囲：0. 5 0 ~ 2 0. 0 k P a (スプリング交換要) (Applicable Outlet Pressure Range : 0.50~20.0kPa (Each spring has a different specific set point range within this range.))</li> </ul>		

DATE: May.12.2016

**Ⓢ I·T·O株式会社**  
〔 Ⓢ I·T·O Corporation 〕

東大阪市箱殿町10番4号  
(10-4 Hakodono-cho, Higashi-Osaka City, Japan)  
TEL:072-981-3781 FAX:072-987-6590