

# 仕 様 書

## Specification

項 目 Item	内 容 Specifications		
名 称 Type	自動切替式分離型調整器 (発信機能付) Separate Type First Stage Automatic Change-over Regulator (With Signal Transmitting Function)		
型 式 Model	T A X - 3 0 A - 0		
容 量 Capacity	3 0 k g / h (C <sub>3</sub> H <sub>8</sub> )		
入口圧力 Inlet Pressure	0. 1 0 ~ 1. 5 6		M P a
出口圧力 Outlet Pressure	0. 0 3 2 ~ 0. 0 8 3		M P a
閉塞圧力 Lockup Pressure	0. 0 9 5		M P a 以下 or less
気密 Air-Tightness Test	入口側 Inlet	1. 8 0	M P a
	出口側 Outlet	0. 1 5	M P a
耐圧 Hydrostatic Test	入口側 Inlet	2. 7 0	M P a
	出口側 Outlet	0. 8 0	M P a
入口接続 Inlet Connection	J I S 2 0 K 1 5 A		フランジ Flange
出口接続 Outlet Connection	R c 1 / 2		
面間寸法 Spacing Dimension	ヨコ (W) 2 5 0 × タテ (H) 6 0 mm		
使用温度範囲 Working Temperature Range	- 2 5 ~ 6 0		℃
質量 Product Weight	約 Approx.	3. 5	k g
補給開始圧力 Starting Pressure of Replenishment	0. 1 0 M P a		未満 less
備考 Note	シグナル自己保持機構付き Signal Self-holding Type		

DATE: Apr.1.2014

**Ⓢ I·T·O株式会社**

〔 **Ⓢ I·T·O Corporation** 〕

東大阪市箱殿町 1 0 番 4 号  
(10-4 Hakodono-cho, Higashi-Osaka City, Japan)  
TEL:072-981-3781 FAX:072-987-6590