

仕 様 書

Specification

項 目 Item	内 容 Specifications		
名 称 Type	自動切替式分離型調整器 (発信機能付) Separate Type First Stage Automatic Change-over Regulator (With Signal Transmitting Function)		
型 式 Model	T A X - 7 0 - 0		
容 量 Capacity	7 0 k g / h (C ₃ H ₈)		
入口圧力 Inlet Pressure	0 . 1 0 ~ 1 . 5 6		M P a
出口圧力 Outlet Pressure	0 . 0 3 2 ~ 0 . 0 8 3		M P a
閉塞圧力 Lockup Pressure	0 . 0 9 5		M P a 以下 or less
気密 Air-Tightness Test	入口側 Inlet	1 . 8 0	M P a
	出口側 Outlet	0 . 1 5	M P a
耐圧 Hydrostatic Test	入口側 Inlet	2 . 7 0	M P a
	出口側 Outlet	0 . 8 0	M P a
入口接続 Inlet Connection	J I S 2 0 K 2 0 A		フランジ Flange
出口接続 Outlet Connection	R 1		
面間寸法 Spacing Dimension	ヨコ (W) 3 3 0 × タテ (H) 1 6 0 mm		
使用温度範囲 Working Temperature Range	- 2 5 ~ 6 0		℃
質量 Product Weight	約 Approx.	9 . 8	k g
補給開始圧力 Starting Pressure of Replenishment	0 . 1 0		M P a 未満 less
備考 Note			

DATE: Feb.19.2016

 I.T.O株式会社

[** I.T.O Corporation**]

東大阪市箱殿町 1 0 番 4 号
(10-4 Hakodono-cho, Higashi-Osaka City, Japan)
TEL:072-981-3781 FAX:072-987-6590